



<p><b>FAED S.R.L.</b></p>	<p align="center"><b>PRODUCT SPECIFICATION CHART</b></p> <p><i>DESCRIPTION:</i> <u>Pneumatic random orbital sander</u> <u>Levigatrice pneumatica orbitale</u></p>	
<p><i>MODEL</i> <b>CR 036 C</b></p> <hr/> <p><i>CODE</i> <b>CR036C/5</b> <b>CR036C/2.5</b></p> 	<p><i>PHOTO/ FOTO:</i></p> 	
<p><i>TECHNICAL NOTE</i> <i>NOTA TECNICA</i></p>	<p>Palm sander with upper lever trigger and side speed regulation. Predisposed for central vacuum dust suction by rotating connection. Built in two version with 2.5mm (CR036/2.5) and 5mm (CR036C/5) orbit</p> <p>Levigatrice palmare con start a leva superiore e regolazione di velocità laterale. Predisposta per aspirazione polveri centralizzata con attacco girevole. Costruita in 2 differenti versioni con orbita 2,5mm (CR036/2.5) e 5mm (CR036/5)</p>	
<p><i>TECHNICAL DATA</i> <i>DATI TECNICI</i></p>	<p>Air pressure / pressione aria Air consumption / consumo aria Air inlet /attacco aria Speed / velocità Pad diameter / diametro platorello Abrasive grip / attacco abrasivo Suction hose / Tubo aspirazione Orbit diameter / diametro orbita Orbit diameter / diametro orbita Total weight w/pad / peso TOT c/platorello Pad weight / peso platorello Dimensions L x D x H</p>	<p>6.3 bar 420 l/min 1/4 " G. 10.000 r.p.m. D.150 mm. Velstick D.29 mm. 2.5 mm (CR036/2.5) 5 mm (CR036/5) 880 g. 130 g.(+5g.) 200 x 150 x 105 mm.</p>
<p><i>SAFETY DATA</i> <i>DATI SICUREZZA</i></p>	<p>Start Stop</p> <p>Noise level /rumorosità N. level on duty /rumor. a lavoro Vibration / Vibrazioni</p>	<p>top lever / leva superiore automatic at lever is release / automatico al rilascio</p> <p>dB(A) 86 dB(A) 84 &lt; 2.5 m/sec<sup>2</sup></p>